

# Positioning Devices

**COMPANY**

**HILTI INC**

7250 Dallas Pky , Legacy Tower Suite 1000  
Plano, TX 75024 United States

E201485

**Fixing Devices Investigated to ANSI/UL 62275**

Cat. No.	Type	Mechanical Str. N	Hole Dia. mm		Panel Thick. mm	Operating Temp. °C		Resistant to UV Light	Air Handling Spaces	IEC 62275 Type
			Min	Max		Min	Max			
<b>Fixing Device</b>										
X-ECT	21	111	-	-	-	0	65	-	AH-2	-

**Positioning Devices Investigated to ANSI/UL 1565**

Catalog No.	Maximum Use Temp, °C
<b>Cable Clamps</b>	
X-ECH/FR-L+	65
X-ECH/FR-M+	65
X-ECH/FR-S+	65
X-EKSC 16	65
X-EKSC 20	65
X-EKSC 25	65

<b>X-EKSC 32</b>	65
<b>X-EKSC 40</b>	65

+ - May be followed by U37 indicating the clamp is provided with the optional steel pin fasteners.

Last Updated on 2023-05-17

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2023 UL LLC."