

FIRESTOP CAVITY BARRIER CFS-VB E60 25MM

Product Information



FIRESTOP CAVITY BARRIER CFS-VB E60 25mm





Applications

- Sealing building envelope cavities to better prevent the spread of fire via the façade
- Firestopping ventilated rainscreen cladding while leaving an air gap of up to 25mm
- Verified fire resistance for 60 minutes integrity and 30 minutes insulation according to ASFP TGD19

Advantages


- Faster installations new push-to-fit bracket system eliminates bending, cutting, and trimming, so you can install up to 40% faster than standard brackets
- Reduced rework strengthened brackets help prevent barrier sagging for fewer adjustments
- Extensive test evidence tested and approved for a wide variety of specialty applications
- Full system solution pair with Hilti façade substructures and anchors for an all-in-one solution for non-ventilated façades
- Direct fastening tested combine with our range of direct fastening solutions for even faster installations

Technical data

Standards	ASFP TGD-19, EN 13501-1		
Base materials	Concrete, Masonry, SFS		
Length	1200 mm		
Thickness	80 mm		
Mineral wool density	80 kg/m3		
Void range	50-400 mm		
E/I (ASFP TGD-19)	60/30		
Reaction to fire (EN 13501-1) A1*			
Durability (EOTA TR024)	Type X**		
Mold and Mildew	Class 0 (ASTM G21, ISO 846		
Performance	Method A)		
Thermal Conductivity	λ= 0.039 W/(mK)*		
Shelf life	No restrictions		
Storage and transport temperature	-20 °C to 60 °C		

^{*}Refers to the mineral wool component

**Refers to the intumescent component



Product options

Product Name	Void Width	Sales Pack Quantity	Item Number
Cavity barrier CFS-VB E60 75+25	100	25 pc	2395732
Cavity barrier CFS-VB E60 125+25	150	15 pc	2395733
Cavity barrier CFS-VB E60 175+25	200	10 pc	2395734
Cavity barrier CFS-VB E60 225+25	250	5 pc	2395735
Cavity barrier CFS-VB E60 275+25	300	5 pc	2395736
Cavity barrier CFS-VB E60 325+25	350	5 pc	2395737
Cavity barrier CFS-VB E60 375+25	400	5 pc	2395738

11/2024



Accessories

Product Name	Sales Pack Quantity	Item Number	
Bracket CFS-VB/NVB S Stainless Steel	60 pc	2420816	
Bracket CFS-VB/NVB M Stainless Steel	60 pc	2420932	
Bracket CFS-VB/NVB L Stainless Steel	60 pc	2420933	77.
Bracket CFS-VB/NVB S Galv. Steel	60 pc	2420826	,
Bracket CFS-VB/NVB M Galv. Steel	60 pc	2420844	
Bracket CFS-VB/NVB L Galv. Steel	60 pc	2420934	

11/2024